



Cerno's product development team prioritized the utility of the Allavo vanity, while not ignoring the importance of the aesthetic. Drawing from our experience with product photography, we knew that a large diffuse light source was the key to achieving our goal. The novel design uses indirect lighting that bounces off a curved metal surface. Cerno's signature use of wood is integrated seamlessly into a design we believe harmonizes usefulness and beauty.



Allavo vanity sconce



Allavo 22 dimensions: 21.3" x 4.6" x 3.9" Allavo 31 dimensions: 30.3" x 4.6" x 3.9" Allavo 40 dimensions: 39.3" x 4.6" x 3.9" Allavo 22 weight: 2 lb - Allavo 31 weight: 2 lb Allavo 40 weight: 3 lb Light source: integrated LED Allavo 22 light output: 780 Lumens (source) Allavo 31 light output: 1170 Lumens (source Allavo 40 light output: 1560 Lumens (source) Light color: 2700 K, 3000 K, 3500 K or 4000 K Color accuracy: 90+ CRI Allavo 22 power usage: 11 W Allavo 31 power usage: 16 W Allavo 40 power usage: 21 W Dimmable (see driver below) Driver location: must be housed in J-box Allavo 22 driver dimensions: 2.63" x 1.25" x 0.8", included Allavo 31 driver dimensions: 3.0" x 1.0" x 1.5", included Allavo 40 driver dimensions: 2.82" x 2.5" x 1.2", included Wood grain will vary. Specifications subject to change. The Allavo can be oriented as a vertical sconce or horizontal sconce. When oriented vertically, a right or left orientation can be achieved by flipping the fixture vertically.

textured black (CM-049) **MATERIAL & FINISH OPTIONS** Allavo part #: 03-250-Size textured white (CM-060) 22" 31" 22 31 40" 40 **Reflector Finish** textured black (CM-049) exterior and textured white (CM-060) interior walnut (CM-001) В textured white (CM-060) exterior Y and interior Wood Finish walnut (CM-001) W dark stained walnut (CM-002) dark stained walnut (CM-002) D white washed oak (CM-095) 0 Metal Finish brushed aluminum (CM-006) A R brushed brass (CM-120) white washed oak (CM-095) Lamping 2700 K LED 27 3000 K LED 30 3500 K LED 4000 K LED 35 40 brushed aluminum (CM-006) Driver 120 V AC input voltage P1 TRIAC, ELV & 0-10 V dimming 277 V AC input voltage P2 TRIAC, FLV & 0-10 V dimming brushed brass (CM-120)

▲ WARNING. California Proposition 65 Warning for California Consumers. This product can expose you to chemicals including wood dust and lead which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.