

Project:									Contact:						
F	Fill in the shaded boxes using the information listed below														
Order Code	R-0030	-		-		-		-		-		-		-	
	MODEL		O DIAMETER		B SUSPENSION		FINISH 1 - RING WALL		FINISH 2 - SEAM PLATE		E LIGHT DIRECTION		E LAMPING CCT		© OPTION CODE
EXAMPLE ORDER CODE	R-0030	-	4	-	S	-	002	-	800	-	D	-	27	-	EM

A DIAMETER




Gaviota, 6' diameter, Angled cables, walnut ring walls, distressed brass seam plate, direct light, 3000K.



Detail of Distressed Brass seam plate with Walnut ring walls

3 3'Ø 4 4'Ø 5 5'Ø 6 6'Ø 7 7'Ø



All Gaviota pendants have 3 seam plates and suspension cables, number of electrical cords per model listed on page 2.

B SUSPENSION











C FINISH 1- RING WALL

001 Walnut

002 Dark Stained Walnut

095 White Washed Oak

012 Brushed Aluminum

046 Rose Gold

047 Brushed Brass

096 Distressed Brass

085 Matte Black

121 Matte White

(D) FINISH 2 - SEAM PLATE

119 Brushed Aluminum

120 Brushed Brass

117 Distressed Brass

049 Textured Black

060 Textured White

Canopy finish will match seam plate finish.

Walnut and Oak fixtures are constructed of real solid wood with a natural oil finish.

(E) LIGHT DIRECTION

D Direct

B Direct and Indirect

(F) LAMPING CCT

27 2700K LED

30 3000K LED

35 3500K LED

40 4000K LED

CRI 90+

© OPTION CODE

XD For custom drop lengths add "XD" followed by desired Overall Height in inches at end of order code. Otherwise a standard 96" drop length is provided which is field cuttable.

EM Emergency Backup option.









LUMEN OUTPUT / WATTAGE / WEIGHT

Direct Light

DIAMETER	WATTS	DELIVERED LUMENS (DOWN)	NUMBER OF DRIVERS	WEIGHT (LBS)	NUMBER OF ELECTRICAL CORDS
3′	74	4622	1	21	1
4′	100	6162	2	26	2
5′	124	7703	2	30	2
6′	151	9419	2	33	2
7′	177	11041	2	38	2

Direct and Indirect Light

DIAMETER	WATTS	DELIVERED LUMENS (DOWN)	DELIVERED LUMENS (UP)	NUMBER OF DRIVERS	WEIGHT (LBS)	NUMBER OF ELECTRICAL CORDS
3′	110	4622	3165	2	21	2
4′	148	6162	4240	3	26	3
5′	183	7703	5320	3	30	3
6′	224	9419	6515	3	33	3
7′	263	11041	7670	3	38	3

CANOPY, SUSPENSION CABLES AND ELECTRICAL CORDS

- The Gaviota is built in 3 sections and is assembled on site (except for 3' diameter).
- 1/16" aircraft cable with cable grip suspension hardware included.
- 96" drop provided for a suspension types add XD in order code for longer drops.
- 24" minimum drop for angled cable suspensions.
- Angled suspension cable angles not to be less than 30 degrees from horizontal.
- Canopies match seam plate material finish.

DRIVER SPECS


120-277 V AC Input

0-10 V dimming down to 1% with dim to off

Drivers to be mounted remote at a maximum distance of 50' including pendant drop distance, provided a 12 gauge wire is used.


Driver dimension are maximum 6.25" x 3" x 1.06".

PHOTOMETRIC POLAR GRAPH





Straight Suspension Canopy 5" Ø X .29"H



Angled Suspension Canopy 8" Ø X 2"H



Collared Suspension Canopy 8" Ø X 1.7"H Collar 6" Ø X .25"H



© FINISH 1 - RING WALL



Walnut CM-001



Dark Stained Walnut CM-002



White Washed Oak CM-095



Brushed Aluminum
CM-012



Rose Gold CM-046



Brushed Brass CM-047



Distressed Brass CM-096



Matte Black
CM-085



Matte White CM-121

(D) FINISH 2 - SEAM PLATE



Brushed Aluminum CM-119



Brushed Brass CM-120



Distressed Brass CM-117



Textured Black Powder Coat CM-049



Textured White Powder Coat CM-060