

Project

Contact

Fill in the shaded boxes using the information listed below

Order
Code

R-0060

(A) SUSPENSION

(B) EXTERIOR
SHADE FINISH

(C) INTERIOR
SHADE FINISH

(D) LIGHT
ENGINE DISC

(E) LAMPING
CCT

(F) LIGHT
OUTPUT

(G) OPTION
CODE

MODEL

EXAMPLE
ORDER CODE

R-0060

-

R

-

049

-

060

-

095

-

30

-

F

-

EM




Textured Black exterior, Textured White interior, Walnut light engine disc, 3000K.




Distressed Brass exterior, Brushed Brass interior, White Washed Oak light engine disc.




Textured White exterior, Textured White interior, Walnut light engine disc.



(1) 1/4"Ø cord
(3) 1/16"Ø suspension cables




Light Engine Disc



6' Tall Person

(A) SUSPENSION


W Corded
White



B Corded
Black

Canopy color will match cord color.

R Rigid
Stem



Rigid stem and canopy matches finish of shade exterior.

(B) EXTERIOR SHADE FINISH

049 Textured Black

060 Textured White

119 Brushed Aluminum

120 Brushed Brass

117 Distressed Brass

(C) INTERIOR SHADE FINISH

060 Textured White

119 Brushed Aluminum*

120 Brushed Brass*

117 Distressed Brass*

*Finish will reduce delivered lumens.

(D) LIGHT ENGINE DISC

001 Walnut

002 Dark Stained Walnut

095 White Washed Oak

049 Textured Black

060 Textured White

119 Brushed Aluminum

120 Brushed Brass

117 Distressed Brass

(E) LAMPING CCT

27 2700K LED

30 3000K LED

35 3500K LED

40 4000K LED

CRI 90+

(F) LIGHT OUTPUT

F Full Output - Wattage

R 50% Reduced Output - Wattage

C Custom Reduction Percentage

Full output:
1945 Lumens (delivered)
30 Watts

Custom Reduction
Percentage to reduce
both lumens and
wattage.

Full output based on
Textured White shade
interior with 3000K.

(G) OPTION CODE

XD For custom drop lengths add "XD" followed by desired *Overall Height* in inches at end of order code. Otherwise a standard 72" drop length is provided which is field cuttable.

EM Emergency Backup option.




FIXTURE SPECS

Dimensions: 28" Ø x 12.75"
Materials: Spun Aluminum Shade, Solid Wood or Spun Metal Accent,
Protective Powder Coated Finishes
Product weight: 19 lb
Light source: Integrated LED
Light output: 1945 Lumens (Textured White shade interior)
Color accuracy: 90+ CRI

DRIVER SPECS


120-277VAC Input
0-10V dimming down to 1% with dim to off
LED driver integrated into fixture

SUSPENSION



Corded Suspension
Canopy 5" Ø X 2"H


- Textured White (CM-060) or Textured Black (CM-049)
- 3x 1/16" Stainless Steel Cables (CM-053)
- Field adjustable drop length: 1'0" min - 8'0" max
- Suitable for a sloped ceiling up to 30 degrees
- For extended cable length, please specify using XD designator in SKU builder
- 5-Conductor SVT Cable - color to match canopy (3 wires for AC power & ground, 2 wires for 0-10V dimming control)



Rigid Suspension
Canopy 8" Ø X 0.38"H

- Stem and canopy finish to match exterior shade finish
- 0.5" Ø rigid stem black or white
- Field cuttable: 1'0" min - 8'0" max
- Suitable for a sloped ceiling up to 30 degrees
- For extended stem length, please specify using XD designator in SKU builder
- White 5-Conductor SVT Cable inside rigid stem (3 wires for AC power & ground, 2 wire for 0-10V dimming control)

PHOTOMETRIC POLAR GRAPH



Ⓑ EXTERIOR SHADE FINISH

				
Textured Black Powder Coat CM-049	Textured White Powder Coat CM-060	Brushed Aluminum CM-119	Brushed Brass CM-120	Distressed Brass CM-117

Ⓒ INTERIOR SHADE FINISH

			
Textured White Powder Coat CM-060	Brushed Aluminum CM-119	Brushed Brass CM-120	Distressed Brass CM-117

Ⓓ LIGHT ENGINE DISC FINISH

			
Walnut CM-001	Dark Stained Walnut CM-002	White Washed Oak CM-095	Textured Black Powder Coat CM-049
			
Textured White Powder Coat CM-060	Brushed Aluminum CM-119	Brushed Brass CM-120	Distressed Brass CM-117