






## Tempus sconce












Product weight: 2 lb Light source: integrated LED Light output: 1280 Lumens (source) Light color: 2700 K, 3000 K, 3500 K, or 4000 K Color accuracy: 90+ CRI Power usage: 14 W Wood grain will vary Specifications subject to change

Dimensions: 12" x 7.75" x 3"






Tempus part # 03-280-Wood Body walnut (CM-001) w dark stained walnut (CM-002) D white washed oak (CM-095) 0 Lamping 2700 K LED 27 3000 K LED 30 3500 K LED 35 4000 K LED 40 Driver AC Input Voltage Range: 120-277 V 120 V input: TRIAC, ELV & 0-10 V Р1 dimmable 240 & 277 V input: only 0-10 V dimmable

Includes frosted polymer (CM-057)

The Tempus Sconce draws inspiration from nature's beautiful designs. The rounded profile, rounded edges, and ample but smooth diffuse light exudes warmth. The solid wood body highlights the elegance of the wood grain. The design is dynamic, working well in traditional, transitional, or sleek modern environments.


Nick Sheridan Designer


white washed oak



# **SPECIFICATION SHEET**










### PHOTOMETRIC POLAR GRAPH



Maximum Candela = 168 Located at Horizontal Angle = 180 Vertical Angle = 67.5

Output specifications shown for 2700K CCT and walnut finish for vertical planes through 180-0 horizontal angles. Other CCTs and material finishes may cause output specifications to vary.

### **FINISHES**



walnut (CM-001)



white washed oak (CM-095)



dark stained walnut (CM-002)

### **TECHNICAL SPECIFICATIONS**

Light source: integrated LED Light output: 1280 Lumens (source)

Light color: 2700 K, 3000 K, 3500 K, or 4000 K

Input voltage: 120-277 V AC Color accuracy: 90+ CRI Power usage: 14 W

Dimmability: TRIAC, ELV, or 0-10V at 120 V AC input

0-10V only at 240-277 V AC input Materials: solid wood, polymer Wood grain will vary

Specifications subject to change



