



WEIGHT / LUMEN OUTPUT / WATTAGE / CORDS / CABLES

Fixture Height	Number of Sides	Weight (Lbs.)	Lumens (Source)	Wattage	Number of Drivers	Number of Cords (SVT)	Numbers of Suspension Cables
40"	3	25	4475	38	1	1	3
	4	33	5970	48	1	1	3
64"	3	32	7665	63	1	1	3
	4	42	10235	83	1	1	3


CANOPY SUSPENSION CABLES AND ELECTRICAL CORDS

Canopy dimensions: 7"Ø x

2" H

3 suspension cables

1 electrical cord



Maximum standard drop length: 96"

Provide additional blocking for attaching mounting plate to ceiling per local code.

If a central all-thread stud is used for support, the driver may not fit within the canopy and will need to be remotely located

DRIVER SPECS

120-277 V AC input:


0-10 V dimming down to 1% with dim to off  
Driver located inside of canopy

Driver dimensions:

40" options: 5.0" x 2.5" x 1.1"

64" options: 6.3" x 3.1" x 1.1"

PHOTOMETRIC POLAR GRAPH



© FINISH 1 - WOOD BODY



Walnut  
CM-001



Dark Stained Walnut  
CM-002



White Washed Oak  
CM-095

© FINISH 2 - METAL



Brushed Aluminum  
CM-119



Brushed Brass  
CM-120



Distressed Brass  
CM-117