
ARCHITECTURAL

TORREY LED CEILING MOUNT

Project	ect						Contact						
F	Fill in the shaded boxes using the information listed below												
Order Code	R-0055	-		-		-		-		-		-	
_	MODEL		(A) EXTERIOR SHADE FINISH		INTERIOR SHADE FINISH		C LIGHT ENGINE DISC		LAMPING CCT		E LIGHT OUTPUT		© OPTION CODE
EXAMPLE ORDER CODE	R-0055	-	049	-	120	-	002	-	35	-	F	-	EM





(A) EXTERIOR SHADE FINISH

049	Textured Black						
060	Textured White						
119	Brushed Aluminum						
120	Brushed Brass						
117	Distressed Brass						
^(B) INTERIOR SHADE FINISH							
060	Textured White						
119	Brushed Aluminum						
120	Brushed Brass						
117	Distressed Brass						
© LIGHT ENGINE DISC							
001	Walnut						
002	Dark Stained Walnut						
095	White Washed Oak						
049	Textured Black						
060	Textured White						

- **Brushed Brass**
- 117 Distressed Brass

119 Brushed Aluminum 6' Tall Person 120 white outside, white inside, white washed oak light engine disc, 3000 K. Photometric Polar Graph Shade Light Engine Disc LAMPING CCT **(E)** LIGHT OUTPUT **(F) OPTION CODE EM** Emergency Backup option. 2700K LED Full Output / Wattage **Custom Reduction** 27 F Percentage to reduce 30 3000K LED R 50% Reduced Output / Wattage both lumens and wattage. 3500K LED Custom Reduction % 35 С 40 4000K LED Full output: Full output based on 2275 Lumens (delivered) . Textured White shade CRI 90+ 37 Watts interior with 3000K.

c(VL)us

Specification subject to change without notice. The information contained in this drawing is the sole property of Cerno LLC. Any reproduction in part or in whole without the written permission of Cerno LLC is prohibited. © 2025 Cerno, L.L.C. All Rights Reserved. | 05.2025 949.715.1534 | SALES@CERNOGROUP.COM



TORREY LED CEILING MOUNT

FIXTURE SPECS

Dimensions: 30" Ø x 5.75"

Materials: Spun Aluminum Shade, Solid Wood or Spun Metal Accent, Protective Powder Coated Finishes Product weight: 13 lb Light source: Integrated LED Light output: 2275 Lumens (Textured White shade interior) Color accuracy: 90+ CRI

DRIVER SPECS

120-277 V AC Input 0-10 V dimming down to 1% with dim to off LED driver integrated into fixture

A EXTERIOR SHADE FINISH

