


$\bigcirc \bigcirc \bigcirc \bigcirc \bigcirc \circ$

TORREY - LED PENDANT

Project								Contact						
F	Fill in the shaded boxes using the information listed below													
Order Code	R-0050	-			-		-		-		-		-	
	Model		O SUSPENSION	B EXTERIOR SHADE FINISH		C INTERIOR SHADE FINISH		D LIGHT ENGINE DISC		E LAMPING CCT		ELIGHT OUTPUT		G OPTION CODE
EXAMPLE ORDER CODE	R-0050	-	R	049	-	060	-	001	-	30	-	F	-	EM








Light Engine Disc





Canopy color will match cord color.



Rigid stem and canopy matches finish of shade exterior.

(B) EXTERIOR SHADE FINISH

- 049 Textured Black060 Textured White
- **119** Brushed Aluminum
- 120 Brushed Brass
- 117 Distressed Brass

C INTERIOR SHADE FINISH

- 060 Textured White
- 119 Brushed Aluminum
- 120 Brushed Brass
- 117 Distressed Brass

*finish will reduce delivered lumens.

D LIGHT ENGINE DISC

- 001 Walnut
- **002** Dark Stained Walnut
- 095 White Washed Oak
- 049 Textured Black
- 060 Textured White
- 119 Brushed Aluminum
- 120 Brushed Brass
- 117 Distressed Brass

© OPTION CODE

- **XD** For custom drop lengths add "XD" followed by desired *Overall Height* in inches at end of order code. Otherwise a standard 72" drop length is provided which is field cuttable.
- **EM** Emergency Backup option.



Torrey pendant, corded, textured black outside, distressed brass inside, walnut light engine disc, 3000 K.



Torrey pendant, corded, textured white outside, textured white inside, white washed oak light engine disc, 3000 K.

(E) LAMPING CCT

2700K LED

3000K LED

3500K LED

4000K LED

27

30

35

40

CRI 90+

(F) LIGHT OUTPUT

- F Full Output Wattage
- **R** 50% Reduced Output Wattage
- C Custom Reduction Percentage
- Full output: 2275 Lumens (delivered) 37 Watts

Custom Reduction Percentage to reduce both lumens and wattage.

Full output based on Textured White shade interior with 3000K.

© 2021 Cerno LLC. All rights reserved. Specification subject to change without notice. The information contained in this drawing is the sole property of Cerno LLC. Any reproduction in part or in whole without the written permission of Cerno LLC is prohibited.

SALES@CERNOGROUP.COM - 949.715.1534

C⊖∩∩O° ARCHITECTURAL

Fixture Specs

Dimensions: 30" Ø x 5.25"

Materials: Spun Aluminum Shade, Solid Wood or Spun Metal Accent, Protective Powder Coated Finishes

Product weight: 13 lb

Light source: Integrated LED

Light output: 2275 Lumens (Textured White shade interior) Color accuracy: 90+ CRI

Suspension



Corded Suspension Canopy 5"ØX 2"H

- Textured White (CM-060) or Textured Black (CM-049)
- 3 x 1/16" Stainless Steel Cables (CM-053)
- Field adjustable drop length: 1'0" min 8'0" max
- Suitable for a sloped ceiling up to 30 degrees
- For extended cable length, please specify using XD designator in SKU builder
- 5-Conductor SVT Cable color to match canopy
- (3 wires for AC power & ground, 2 wire for 0-10V dimming control)

Driver Specs


120-277 V AC Input 0-10 V dimming down to 1% with dim to off LED driver integrated into fixture



Rigid Suspension Canopy 8" Ø X 0.38"H

- Stem and canopy finish to match exterior shade finish
- 1" Ø rigid stem
- Field cuttable: 1'0" min 8'0" max
- For extended stem length, please specify using XD designator in SKU builder
- White 5-Conductor SVT Cable inside rigid stem
- (3 wires for AC power & ground, 2 wire for 0-10V dimming control)

Photometric Polar Graph





B EXTERIOR SHADE FINISH



© INTERIOR SHADE FINISH





CM-060 Textured White Powder Coat





CM-120 Brushed Brass



CM-117 Distressed Brass

LIGHT ENGINE DISC FINISH



CM-001 Walnut

CM-119

Brushed Aluminum



CM-002 Dark Stained Walnut



CM-120 Brushed Brass



CM-095 White Washed Oak



CM-117 Distressed Brass



CM-049 Textured Black Powder Coat



CM-060 Textured White Powder Coat