





Torrey pendant, corded, textured black outside, distressed brass inside, walnut light engine disc, 3000 K.



Torrey pendant, corded, textured white outside, textured white inside, white washed oak light engine disc, 3000 K.







A SUSPENSION

Corded White



Canopy color will match cord color.

Rigid R Stem



Rigid stem and canopy matches finish of shade exterior.

(B) EXTERIOR SHADE FINISH

049 Textured Black

060 Textured White

Brushed Aluminum 119

120 Brushed Brass

117 Distressed Brass

O INTERIOR SHADE FINISH

060 Textured White

119 Brushed Aluminum

120 Brushed Brass

117 Distressed Brass

*finish will reduce delivered lumens.

(1) LIGHT ENGINE DISC

001 Walnut

002 Dark Stained Walnut

095 White Washed Oak

049 Textured Black

060 Textured White

Brushed Aluminum 119

120 Brushed Brass

117 Distressed Brass

(E) LAMPING CCT

2700K LED

3000K LED 30

3500K LED 35

40 4000K LED

CRI 90+

(F) LIGHT OUTPUT

Full Output - Wattage

50% Reduced Output - Wattage R

C **Custom Reduction Percentage**

Full output: 2275 Lumens (delivered) 37 Watts

Custom Reduction Percentage to reduce both lumens and wattage.

Full output based on Textured White shade interior with 3000K.

© OPTION CODE

XD For custom drop lengths add "XD" followed by desired Overall Height in inches at end of order code. Otherwise a standard 72" drop length is provided which is field cuttable.

EM Emergency Backup option.













Fixture Specs

Dimensions: 30" Ø x 5.25"

Materials: Spun Aluminum Shade, Solid Wood or Spun Metal Accent,

Protective Powder Coated Finishes

Product weight: 13 lb

Light source: Integrated LED

Light output: 2275 Lumens (Textured White shade interior)

Color accuracy: 90+ CRI

Driver Specs

120-277 V AC Input

0-10 V dimming down to 1% with dim to off

LED driver integrated into fixture

Suspension



Corded Suspension Canopy 5" Ø X 2"H


- Textured White (CM-060) or Textured Black (CM-049)
- 3 x 1/16" Stainless Steel Cables (CM-053)
- Field adjustable drop length: 1'0" min 8'0" max
- Suitable for a sloped ceiling up to 30 degrees
- For extended cable length, please specify using XD designator in SKU builder
- 5-Conductor SVT Cable color to match canopy (3 wires for AC power & ground, 2 wires for 0-10V dimming control)



Rigid Suspension Canopy 8" Ø X 0.38"H

- Stem and canopy finish to match exterior shade finish
- -0.5" Ø rigid stem
- Field cuttable: 1'0" min 8'0" max
- Suitable for a sloped ceiling up to 30 degrees
- For extended stem length, please specify using XD designator in SKU builder
- White 5-Conductor SVT Cable inside rigid stem (3 wires for AC power & ground, 2 wire for 0-10V dimming control)

Photometric Polar Graph






® EXTERIOR SHADE FINISH



CM-049 Textured Black Powder Coat



CM-060 Textured White Powder Coat



CM-119 Brushed Aluminum



CM-120 Brushed Brass



CM-117 Distressed Brass

O INTERIOR SHADE FINISH



CM-060 Textured White Powder Coat



CM-119 Brushed Aluminum



CM-120 Brushed Brass



CM-117 Distressed Brass

D LIGHT ENGINE DISC FINISH



CM-001 Walnut



CM-002 Dark Stained Walnut



CM-095 White Washed Oak



CM-049 Textured Black Powder Coat



CM-060 Textured White Powder Coat



CM-119 Brushed Aluminum



CM-120 Brushed Brass



CM-117 Distressed Brass