




Veris was a concept we started exploring ten years ago. Two offset layers of petals simultaneously shield the light source while allowing reflected light to wash the inside petals, creating a dramatic ambient luminaire. The form materializes through a series of processes that utilize cutting edge CNC laser technology but still rely on skilled hand-rolling and bending of the aluminum petals.

Veris 34 pendant



Dimensions: 33.5" Ø, 23" Product weight: 8 lb Suitable for a sloped ceiling

Integrated LED Specifications

Light output: 2815 Lumens (source) Light color: 2700 K, 3000 K, 3500 K or 4000 K Color accuracy: 90+ CRI Power usage: 132.5 W Dimmable (see driver below)

Dimmable (see driver below)
Driver must be housed in J-box
Driver dimensions: 3.3" x 2.4" x 1", included

E26 Medium Base Specifications

Lamping: 3x E26 base, type A lamp, 60 W max Input voltage: 250 V AC max Bulb not included

Textured Black (CM-049) extended round canopy with SVT-3 Cable, Black (CM-039) and 1/16" Stainless Steel Cables (CM-053)
Canopy dimensions: 5" Ø, 2"
See website for more canopy information
Field adjustable drop length: 1.0" min - 8'0" max
Specifications subject to change



MATERIAL & FINISH OPTIONS

AC Input Voltage Range: 120-277 V 120 V input: TRIAC, ELV & 0-10 V dimmable 240 & 277 V input: only 0-10 V dimmable

Shade Material matte black (CM-085) with В matte white interior brushed aluminum (CM-012) Α brushed rose gold (CM-046) G brushed brass (CM-047) R distressed brass (CM-096) D gloss white (CM-054) w Lamping* 2700 K LED 27 3000 K LED 35 3500 K L FD 30 4000 K LED 40 medium base E26 socket MB Driver (LED version only)

Veris 34 pendant part # 06-260-34





extended round canopy w/ SVT-3 cable and steel cables



matte black (CM-085) with matte white interior



brushed aluminum (CM-012)



brushed rose gold (CM-046)





gloss white (CM-054)

